



petlink™ net



A Datamars brand

OMNI MAX 360 Universal Scanner

OMNI MAX is our newest, portable, universal scanner with the strongest feature-set of any available microchip scanner - making it a perfect fit for animal identification in any environment.

OMNI MAX has an innovative antenna that runs along the full perimeter of the reader, greatly increasing the read field for fast and easy scanning. With OMNI MAX, PetLink delivers the most modern available technology to ensure the fastest possible microchip ID with every read. Connect the OMNI MAX to a computer via USB or optional Bluetooth wireless connection. The keyboard wedge allows microchip IDs to be transmitted directly to your computer, tablet, or smartphone and any other Windows / Max compatible application as if typed by a keyboard - eliminating the possibility of transcription errors. Communications with your computer, as well as updating the scanner firmware, can be managed through the S-ID software tool, available for download from www.pet.datamars.com.

Highlights

- Reads all available companion animal microchips
- Microchip number remains on-screen until next scan.
- Display scan results on computer, smartphone or tablet - wherever the cursor is placed.
- Easy data transfer via USB or wireless connectivity.
- 360 degree read field leads to quicker microchip detection and faster ID.

Keys to Effective Scanning:

- Hold the scanner close to or touching the animal.
- Scan slowly and repeatedly over the entire body to ensure a microchip is present.
- Wave the scanner back and forth lightly while scanning, (microchips may be in various orientations within the animal).
- Scan first horizontal, then vertical “S” pattern down the animal’s body.
- Consider scanning each animal more than once to ensure any present microchip can be localized by the scanner.

Technical Specifications

Dimensions

- 10.47" x 5.83" x 1.06"

Weight

- 15.52 oz

Operating Temperature

- +23 F to +131 F 95% RH, non-condensing

Frequency

- 134.2 kHz

Storage Temperature

- -4 F to +149 F 95% RH, non-condensing

Battery

- Rechargeable Li-ion battery
- Battery lasts for more than 500 charge cycles

Typical Reading Distance

- FDX-B (134.2 kHz) 7.87"
- FDX-A/Fecava (125 kHz) 4.72"
- Trovan (128 kHz) 1.97"
- Avid Encrypted (125 kHz) 4.72"

Housing

- White plastic, water-resistant with USB cap inserted

Interface

- USB (cable included) / Optional Bluetooth wireless

Memory

- 2GB internal memory

Accreditation

- ISO 11784/5

Questions?

Contact us at (781) 281-2216
or at ussales@petlink.net

DATAMARS

petlink™ net

A Datamars brand

