



Introducing the all new Cavitor[®] line of Ultrasonic Cleaners

- Five Cavitor Cleaner models ranging from 3.1 quarts to 20 gallons.
- Heater included on all models.
- Digital timer and heater displays and controls
- Stainless steel baskets and covers included
- Smudge-free stainless surface on all cleaners
- Drain valves included on all cleaners except 3L.
- Handles on smaller cleaners for easy lifting
- Two fixed wheels and two omnidirectional wheels with locks on 20G
- Adjustable ultrasonic power on 20G



Extra baskets are available for all Cavitor ultrasonic cleaners. Load one basket while the other is processing!

Use baskets to hold items for cleaning and safely remove them from the cleaner when they are finished cleaning.



Mettler Electronics Corp.

www.mettlerelectronics.com






Toll Free: 1.800.854.9305

Extra lids are available for all Cavitor ultrasonic cleaners.

Use lids to trap biologically-active contaminants and reduce noise while the cleaner is in operation.



New Cavitator® Ultrasonic Cleaner Specifications

Mettler P/N	Picture	Description	Included accessories	Power	Timer	Temperature	Tank volume (G)	Tank size-mm (inches)	Dimensions of cleaner-mm (inches)	Weight Kg of the outer cover (lbs)	Material of the cover	Material of Ultrasonic the cover	Watts	Watts / heater
ME 3L		Digital, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110 VAC / 60 Hz or 220 VAC / 50 Hz	0 - 30 minutes	20 - 80°C	3 L (0.8)	240 x 135 x 100 (9.4 x 5.3 x 3.9) SUS304	270 x 170 x 210 (10.6 x 6.7 x 8.3)	4 (8.8)	Stainless steel	Stainless steel	120 W	100 W
ME 6L		Digital, drainage ball valve, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110 VAC / 60 Hz or 220 VAC / 50 Hz	0 - 30 minutes	20 - 80°C	6 L (1.6)	300 x 150 x 150 (11.8 x 5.9 x 5.9) SUS304	330 x 180 x 270 (13 x 6.7 x 10.6)	6 (13.2)	Stainless steel	Stainless steel	180 W	200 W
ME 10L		Digital, drainage ball valve, heat dissipation fan, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110 VAC / 60 Hz or 220 VAC / 50 Hz	0 - 30 minutes	20 - 80°C	10 L (2.6)	300 x 240 x 150 (11.8 x 9.4 x 5.9) SUS304	330 x 270 x 270 (13 x 10.6 x 10.6)	8 (17.6)	Stainless steel	Stainless steel	240 W	250 W
ME 22L		Digital, drainage ball valve, heat dissipation fan, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110 VAC / 60 Hz or 220 VAC / 50 Hz	0 - 30 minutes	20 - 80°C	22 L (5.8)	500 x 300 x 150 (19.7 x 11.8 x 5.9) SUS304	550 x 330 x 270 (21.6 x 13 x 10.6)	13 (28.6)	Stainless steel	Stainless steel	480 W	600 W
ME 20G*		Adjustable power control, Fill hose, drain valve, 2 fixed wheels and 2 omni-directional wheels with locks, heat dissipation fan, SUS 304 stainless steel, CE	Stainless steel basket and cover	110 VAC / 60 Hz or 220 VAC / 50 Hz	0 - 30 minutes	20 - 80°C	78 L (20)	550 x 400 x 350 (21.7 x 15.7 x 13.8) SUS304	650 x 450 x 620 (25.6 x 17.7 x 24.4)	45 (99)	Stainless steel	Stainless steel	1,200 W	1,000 W

* The ME20G has a 125V 20 A, NEMA 5-20, Hospital Grade Plug, which will only plug into a special 115V, 20A amp outlet



Mettler Electronics Corp.